



# Fontemagna

Fontemagna I.T.	FIZZ
Capacidade de arrefecimento	150 (lt/h)
Fornecimento contínuo	80 (lt)
Temperatura água fria	3 - 10°C
Ice bank capacity	18 (lt)
Ice bank	8 kg
Cooling technology	ICE BANK - Double Stainless Steel coil
Condensation	Forced ventilation (Fan)
Adjustable Thermostat	Yes
Refrigerant Gas	Natural HYDROCARBON gas R290
Compressor Power	700 kcal/h
Pump	Professional carbonator pump
Inlet water Pipe	ø 3/8" x 1/4"
Inlet Co2 Pipe	ø 8 x 1 mm
Dispensing area height He	305 mm
Typology	Floor standing
Supply	220 V - 50 Hz
Power	650 W - 2,6 A (400 W - 1,6 A Steel)
Working Room Temperature	Min 5°C - Max 42°C
NET WEIGHT	50 kg (45 kg Steel)
GROSS WEIGHT	55 kg (50 kg Steel)
Dimensions L x W x H	520 x 505 x 1450 mm
Packaging dimensions	600 x 600 x 1630 mm
Dispensing	3 supply option (sparkling, cold and room temperature water) with customizable portion control system
Push buttons	Stainless steel push buttons
Energy saving device	Included, dedicated push buttons
Display Allarms	No water, No CO2
Materials	All robust Stainless steel and aluminum parts
Other features	Safety inlet valve Anti -splash drip tray Co2 pressure reducer included Predisposition for fixing filters and Co2 Cylinder (OPTIONALS) inside the machine

d'água

Estrada de Manique 1232,  
Armazém 1  
2645-551 Alcabideche  
Telefone 707 255 000  
(+351) 214 604 100  
Fax 707 255 001  
(+351) 214 604 199  
comercial@dagua.pt

**PMS**  
SOLUTIONS